

## WRENCHES & PIPE VICES

### Leader Pattern Pipe Wrenches




The frame and handle are made from a one piece ductile iron casting which is guaranteed unbreakable, whilst the flash hardened teeth increase wear resistance. The hardened and tempered steel adjustment nut gives a longer working life and the precision machined screw thread and spring jaw remain open until pressure is applied. Can also be used as a crude hammer. Conforms to British Standard BS3594.



Part No	Length (when open)	Pipe Capacity	Box Qty
ELPW8	8" (200mm)	1" (25mm)	4
ELPW10	10" (250mm)	1½" (38mm)	4
ELPW12	12" (300mm)	2" (51mm)	4
ELPW14	14" (350mm)	2" (51mm)	4
ELPW18	18" (450mm)	2½" (63mm)	4
ELPW24	24" (600mm)	3" (76mm)	1
ELPW36	36" (910mm)	5" (127mm)	1
ELPW48	48" (1200mm)	6" (152mm)	1

### Stillson Pattern Pipe Wrenches



The hardened and tempered hook jaw eliminates breakage, whilst the flash hardened teeth increase wear resistance. The nut abutment means that all loading is transferred direct from the handle to the nut and jaw via the nut abutment, ensuring that the frame is not load bearing, thus reducing the possibility of frame failure. Conforms to British Standard BS3594

Part No	Length (when open)	Pipe Capacity	Box Qty
ESPW8	8" (200mm)	¾" (19mm)	6
ESPW10	10" (250mm)	1" (25mm)	6
ESPW12	12" (300mm)	1½" (32mm)	6
ESPW14	14" (350mm)	1½" (38mm)	6
ESPW18	18" (450mm)	2" (51mm)	4
ESPW24	24" (600mm)	2½" (63mm)	1
ESPW36	36" (910mm)	3½" (89mm)	1