AIR CAULKING GUNS

section 5



1 4243 AIR CAULKING GUN

• For the automotive workshop

Accepts standard size 215 x 50mm cartridges

Bore size	50mm
Tube length	215mm
Operating air pressure	30-60psi (2.1- 4.1bar)
Average air consumption	6.0cfm (170L/min)
Minimum hose size	3/8" I.D
Air Inlet	1/4" BSP
Weight	1.1kg
-	
Stock	

No. 22301



2 4244A AIR UNDERBODY COATING GUN

Easy to use air underbody coating gun (Schutz)
Fits 1 litre "Schutz" type canisters

Fits 1 litre "Schutz" type canisters	
Canister thread (Schutz type)	M42 x 3P
Tube length	215mm
Operating air pressure	90 PSI (6.2bar)
Average air consumption	8.0 CFM (227 L/min)
Minimum hose size	3/8" I.D
Air Inlet	1/4" BSP
Weight	1.4kg

Stock No. 55109



3 4997 400cc HEAVY DUTY AIR GREASE GUN • Continuous flow

- Accepts bulk or standard 400g cartridges
- 360° adjustable handle

Rigid delivery tube

Stock No.

Operating air pressure	30-110psi (2.1-7.6bar)
Average air consumption	2400-4500psi (166-414bar)
Minimum hose size	3/8" I.D
Air Inlet	1/4" BSP
Weight	1.5kg

4 4297 400cc Air grease gun

- Accepts bulk, standard or pump 400g cartridges
- 360° adjustable handle
- Rigid and flexible delivery tube

Operating air pressure	30-110psi (2.1-7.6bar)
Average air consumption	1200-4500psi (83-414bar)
Minimum hose size	3/8" I.D
Air Inlet	1/4" BSP
Weight	1.5kg

Stock No. 33785







6 4288B PISTOL-GRIP AIR INFLATOR

Pistol-grip with dial. Suitable for use with motor vehicles, cycles, dinghies, etc. Clip-on connector. Maximum inflation pressure 8 BAR (115psi). Dial reads 0-12bar and 0-170psi (for guidance only). Display packed. The pressure dial on this model is for guidance only and should be checked with a tyre pressure gauge to BS EN12645

Stock No.

10604



Pistol-grip with dial. Suitable for use with motor vehicles, cycles, dinghies, etc. Clip-on connector. Dial reads 0-10bar and 0-140psi. Carton packed.

The pressure dial on this model is for guidance only and should be checked with a tyre pressure gauge to BS EN12645:1999

Stock No.

27871

