



1 3004A
3/8" Sq. Dr. TORQUE WRENCH 10-80Nm (DISPLAY PACKED)

Ratchet head is engraved with Nm and lb-in scales on the barrel of the wrench. The micrometer type sleeve allows accurate preset torque values to be set. When torque is reached the wrench produces an audible click and a slight release of tension. Range: 10-80Nm/88.5-708lb-in. Overall length 280mm. Calibration certificate included. Supplied in blow mould storage case. Display packed.

Stock No. 34570

2 3004AB
3/8" Sq. Dr. TORQUE WRENCH 10-80Nm (SOLD LOOSE)

Stock No. 54627



1/2" SQ.DRIVE



3/4" SQ.DRIVE

3 3001A
1/2" Sq. Dr. TORQUE WRENCH 30-210Nm

Ratchet head is engraved with Nm and lb-in scales on the barrel of the wrench. The micrometer type sleeve allows accurate preset torque values to be set. When torque is reached the wrench produces an audible click and a release of tension. Marked range: 30-210Nm/22.1-154.9lb-ft. Overall length 475mm. Supplied in blow mould storage case.

| Stock No. | Description |
|-----------|---------------|
| 30357 | Torque Wrench |
| 30752 | Repair Kit |

4 3005A
3/4" Sq. Dr. TORQUE WRENCH 65-450Nm

Ratchet head is engraved with Nm and lb-in scales on the barrel of the wrench with a micrometer type sleeve, allowing accurate preset torque values to be set. When torque is reached the wrench produces an audible click and a release of tension. Marked range: 65-450Nm/48-332 lb-ft. Overall length 840mm. Calibration certificate included. Supplied in blow mould storage case.

Stock No. 34964



1/4" SQ.DRIVE

5 BTW
1/4" Sq. Dr. TORQUE WRENCH 5-25Nm

Easy to use torque wrench. The click-type operation and micrometer adjustment allow the user to apply the correct torque when required. The torque value range is 5-25Nm. Supplied in a blow mould case.

Stock No. 78639



3/8" SQ.DRIVE

6 BTW
3/8" Sq. Dr. TORQUE WRENCH 20-110Nm

Easy to use torque wrench. The click-type operation and micrometer adjustment allow the user to apply the correct torque when required. The torque value range is 20-110Nm. Supplied in a blow mould case.

Stock No. 78641



1/2" SQ.DRIVE

7 BTW
1/2" Sq. Dr. TORQUE WRENCH 30-210Nm

Easy to use torque wrench. The click-type operation and micrometer adjustment allow the user to apply the correct torque when required. The torque value range is 30-210Nm. Supplied in a blow mould case.

Stock No. 78642



3/8" SQ.DRIVE

8 3004A/BK
3/8" Sq. Dr. TORQUE WRENCH 10 - 80Nm
 Supplied with calibration certificate

Reversible ratchet head. The in-lb and Nm scale is engraved on the barrel of the wrench. The micrometer type sleeve allows accurate preset torque values to be set. When torque is reached the wrench produces an audible click and a release of tension. Marked range: 10 - 80Nm and 88.5-708in-lb. Supplied in blow mould storage case.

Stock No. 64534



1/2" SQ.DRIVE

9 3001A/BK
1/2" Sq. Dr. TORQUE WRENCH 30-210Nm
 Supplied with calibration certificate

Reversible ratchet head. The in-lb and Nm scale is engraved on the barrel of the wrench. The micrometer type sleeve allows accurate preset torque values to be set. When torque is reached the wrench produces an audible click and a release of tension. Marked range: 30-210Nm/22.1-154.9 lb-ft. Supplied in blow mould storage case.

Stock No. 64535