



1 GG9 QUICK RELEASE GREASE CONNECTOR

Expert Quality, grease gun connector fitted with a sliding sleeve, easily operated by a thumb lever. This simple yet highly effective mechanism allows for one-handed locked on operation. Designed for use with any type of grease gun up to a maximum pressure of 8,000PSI (550BAR) including manual, pneumatic, cordless and industrial. Works with all styles of head profile grease nipples in metric and SAE. Fitted with 1/8" BSPT female thread.

Stock No. 16156



2 GG8 RIGID DELIVERY TUBE (170mm)

Cranked high pressure zinc plated tube. Complete with hydraulic connector. Suitable for certain Draper Grease Guns. Safe working pressure 400bar/5800psi. Thread 1/8 BSPT. Display packed.

Stock No. 57817



3 GG5 FLEXIBLE DELIVERY TUBE (300mm)

High pressure reinforced rubber tube, threaded 1/8" BSPT at both ends. Safe working pressure 400bar/5800psi. Display packed.

Stock No. 57841



4 GG6 FLEXIBLE DELIVERY TUBE (300mm)

High pressure thermoplastic tube, threaded 1/8" BSPT at both ends. Safe working pressure 240bar/3500psi. Display packed.


Stock No. 12750



5 GNA-M 70 ASSORTED METRIC GREASE NIPPLES

Manufactured from EN-1A steel with profiles to BS, SAE, DIN, JIS and IS. Heat treated to SAE J534 and hardened. Yellow zinc plated to ASTM B117 specification. Display packed in plastic storage box.

Stock No. 43962



6 GNA-BSPT 50 ASSORTED BSPT GREASE NIPPLES

Manufactured from EN-1A steel with profiles to BS, SAE, DIN, JIS and IS. Heat treated to SAE J534 and hardened. Yellow zinc plated to ASTM B117 specification. Display packed in plastic storage box.

Stock No. 43961



7 GG10 HYDRAULIC CONNECTOR

Heavy duty four jaw connector with brass body, threaded 1/8" BSPT. Safe working pressure 400bar/5800psi. Display packed.

Stock No. 12771



8 GG8 HYDRAULIC CONNECTOR

Four jaw plated steel connector, threaded 1/8" BSPT. Safe working pressure 680bar/9800psi. Display packed.

Stock No. 57859



9 GG7 HOOK-ON CONNECTOR

Heavy duty hook or slide-on connector with plated steel body, threaded 1/8" BSP. Safe working pressure 80bar/1150psi. Sold loose.

Stock No. 57875



10 PO1 PRECISION LUBRICATOR

Polished aluminium with steel pocket clip. Designed for pinpoint lubrication to small and awkward areas. 40mm length applicator needle with brass flow control button for fine control. Display packed.

Stock No.	Length
43982	145mm



11 O27 FORCE FEED OIL CANS

Oil cans supplied with fitted flexible spout and a loose interchangeable rigid spout. Sold loose.

Stock No.	Capacity
21716	125ml
21717	200ml
21718	300ml
21719	500ml
21720	700ml



12 OMJ MEASURING JUGS

High density polyethylene. Resistant to diesel/petrol, oils and most acids. Flexible spout with carrying handle and screw top lid. Metric and US imperial graduations on jug body. Sold loose.

Stock No.	Capacity
43963	1L
43964	3L
43965	5L
38362	6L
83999	8L