



**1** 4276

### AIR NIBBLER

Quality diecast construction. Punch head has four way entry for forward, right, left and reverse operation. Carton packed.

Specification:

Cutting capacity	... 18 gauge in steel
Strokes per minute	... 2100
Operating air pressure	... 90psi (6.2bar)
Average air consumption	... 4.0cfm (114L/min)
Minimum hose size	... 3/8" I.D
Air inlet	... 1/4" BSP
Weight	... 1kg

**This machine has a minimum cutting radius of 6mm.**

Stock No.	Description	Price each
27639	Nibbler	
27831	Punch	
27834	Die	



**2** 4202AK

### AIR HAMMER KIT

General purpose short stroke hammer kit comprising a full range of accessories including panel cutter, rivet cutter, bush splitter, spot weld splitter and piercing cutter. Other individual cutters are available separately. Supplied complete in carrying case. Display carton.

Contents: • air hammer • 5 chisels • chisel retaining spring • oil pot • 1/4" BSP nipple

Specification - air hammer:

Chisel shank opening	... 10.18mm	Average air consumption	... 4.0cfm (114L/min)
Blows per minute	... 3000	Minimum hose size	... 3/8" I.D
Stroke length	... 66.6mm	Air inlet	... 1/4" BSP
Operating air pressure	... 90psi (6.2bar)	Weight (hammer only)	... 2 kg

Stock No.	Price per kit
57676	



**3** A4202AK

### CHISEL RETAINING SPRING

For use with air hammers. Display packed.

Stock No.	Price each
22315	



### CHISELS AND FLANGE ATTACHMENT

For use with Stock Nos.57676 as well as other manufacturers similar air hammers. Shank 10.18mm. All chisels must be used with a chisel retaining spring, Stock No.22315. Display packed.

Stock No.	Description	Price each
57800	Tailpipe Cutter Chisel	-
57801	Spot Weld Breaker Chisel	-
57802	Taper Punch	-
57803	Ripping Chisel	-
57804	Panel Cutting Chisel	-
59083	Metal Flanging Attachment	-

### PRODUCT LOCATOR

AIR TOOL HOSES AND FITTINGS - A complete range of air tool hoses and fittings is shown on pages 655-662.