

1 346P WIRE CUP BRUSHES (75mm)

Manufactured from 0.3mm hardened brassed steel wire. Designed for use with angle grinders. The unique rounded edges of the cup prevent the wires breaking whilst in use and thereby prolong the life of the brush and enhance performance. Display packed.

hread
0 x 1.25 4 x 2 0



СВ **TWIST KNOT WIRE CUP BRUSHES**

Manufactured from 0.5mm hardened steel wire. Designed for use with angle grinders. M14 thread.

Stock No.	Dia.	Max. Speed
41447	60mm	11,000r/min
41449	80mm	8500r/min
41450	100mm	8500r/min





5 CB-2

CRIMPED WIRE CUP BRUSHES

Expert Quality, industrial quality manufactured from 0.3mm hardened brassed steel wire. Designed for use with angle grinders. Carton packed.

	-	-		
Stock No.	Dia.	Thread	Max. Speed	
52634	60mm	M10	11,000r/min	
52635 52636 52637 52638	60mm 80mm 100mm 125mm	M14 M14 M14 M14	11,000r/min 8500r/min 8500r/min 7500r/min	



WIRE WOOL (150G)

Wire wool manufactured from steel. Ideal for buffing, cleaning, cutting, and removing. Select the grade required. Display packed.

Stock No.	Grade	
82581	#00 Fine	
82580	#0 Medium Fine	
82579	#1 Medium	



CRIMPED WIRE CUP BRUSHES

Manufactured from 0.3mm hardened brassed steel wire. Designed for use with angle grinders. M14 thread. Display packed.

. , , ,			
Stock No.	Dia.	Max. Speed	
41443 41444 41445	60mm 80mm 100mm	11,000r/min 8500r/min 8500r/min	
41446	125mm	7500r/min	



Rotary grinding stones suitable for use on most metals. Comprising five assorted shapes and abrasive types. Manufactured from aluminium oxide. Maximum working speeds 3000-6000 r/min. Shank diameter 6mm.

MOUNTED GRINDING POINT SET (5 PIECE)

Stock No.			
49301			





4 CB TWIST KNOT WIRE CUP BRUSHES

Expert Quality, industrial quality manufactured from 0.8mm hardened steel wire. Designed for use with angle grinders. Carton packed.

Stock			Max.	
No.	Dia.	Thread	Speed	
52630	60mm	M10	11,000r/min	
52631	60mm	M14	11,000r/min	
52632	80mm	M14	8500r/min	
52633	100mm	M14	8500r/min	



MOUNTED GRINDING POINT SET (5 PIECE)

Rotary grinding stones suitable for use on most metals. Comprising five assorted shapes and abrasive types. Manufactured from aluminium oxide. Maximum running speeds working 7000-8000 r/min. Shank diameter 1/8". Display packed

. , ,		
Stock No.		
49294		

BACKING PADS & DISCS



9 A4207P **RUBBER BACKING PAD (100mm)**

For use with 100mm diameter cutting wheels and grinding discs. 3/8" UNF thread. Sold loose.

	-	
Stock Io.		
7940		



RUBBER BACKING DISC (125mm)

Supplied with 6mm diameter arbor assembly. For use with 125mm diameter sanding discs. Display packed.

Stock No.			
83815			



BACKING PADS

Backing pads for angle grinders. Supplied with locking flange nut. Display packed.

-		-		
Stock No.	Part No.	For Discs Dia.	Thread	
58608 58609 58620	APT8 APT9 APT11	100mm 115mm 125mm	M10 x 1.5 M14 M14	
45976	ΔPT124	180mm	M14	



12 APT118 **BACKING PAD (175mm)**

For use with the angle polishers. M14 thread with hook and loop fixing. Packed in polythene bag with header

Stock No.			
46294			