

10MM KEYLESS AIR DRILL



1 SFSAD KEYLESS AIR DRILL (10mm)

- Low noise, low vibration
- Forward/reverse
- Composite body
- Reduces operator fatigue and the 'cold sink' effect
- Planetary gear system
- 3/8" keyless chuck

Chuck range	10mm
Free speed	2,200 rpm
Operating air pressure	90psi (6.2bar)
Average air consumption	5.5cfm (155L/min)
Vibration level	1.0M/S ²
Min. hose size	3/8" (10mm)
Air inlet	1/4" BSP
Weight	1.48kg

Stock No. 65139

EXPERT QUALITY AIR SCREWDRIVERS



2 5240PRO COMPOSITE AIR SCREWDRIVER

- **Expert Quality**
- Low noise, low vibration
- Composite body
- Reduces operator fatigue and the 'cold sink' effect
- Forward/reverse
- Silenced motor outlet
- Planetary gear system
- Variable speed trigger

Hexagon drive	1/4"
Free speed	1800r/min
Torque	10-90lb-in (1.13-10.17Nm)
Operating air pressure	90psi (6.2bar)
Average air consumption	4cfm (114L/min)
Minimum hose size	3/8" I.D
Air inlet	1/4" BSP
Weight	1.3kg

Stock No. 14193



3 5241PRO COMPOSITE IN-LINE AIR SCREWDRIVER

- **Expert Quality**
- Low noise, low vibration
- Composite body
- Reduces operator fatigue and the 'cold sink' effect
- Forward/reverse
- Silenced motor outlet
- Planetary gear system
- Quick change chuck
- Suspension loop
- Cushion clutch

Hexagon drive	1/4"
Free speed	1800r/min
Torque	10-90lb-in (1.13-10.17Nm)
Operating air pressure	90psi (6.2bar)
Average air consumption	4cfm (114L/min)
Minimum hose size	3/8" I.D
Air inlet	1/4" BSP
Weight	1.2kg

Stock No. 14197

AIR BELT SANDER

NEW



4 DAT-ABS AIR BELT SANDER (10mm)

- Lightweight aluminium housing • Rear exhaust • Lever throttle for added speed control
- Ergonomic soft grip handle • Easy belt replacement
- Suitable for jobs in narrow spaces and recessed corners
- Supplied with 3 different sanding belts (60, 80, 120 grit)

Contents:

- Air belt sander • 60 Grit Sanding belt • 80 Grit Grit Sanding belt
- 120 Grit Grit Sanding belt • 1/4" BSP airline connector

Overall length	280mm
Belt width	10mm
Belt length	330mm
Free speed	18,000rpm
Operating air pressure	90 psi
Average air consumption	6cfm (170L/min)
Vibration level	4.8M/S ²
Minimum hose size (ID)	3/8" (10mm)
Air inlet	1/4" BSP
Weight	0.78kgs

Stock No. 84123



5 A4262 10 x 330mm ALUMINIUM OXIDE SANDING BELTS

Cloth backed. For use with Draper Compact Belt Sander Stock No. 52605 and other manufacturers similar machines. Sold loose.

Stock No.	Grit Grade
30348	40
30349	60
26931	80
26932	120