



1/4" SQ.DRIVE



1 5219PRO

1/4" Sq. Dr. STUBBY COMPOSITE BODY AIR RATCHET

Expert Quality, lower noise, low vibration, low weight with silenced motor outlet for maximum user comfort. The composite body makes this a lightweight but rugged tool that reduces operator fatigue and the 'cold sink' effect. Display carton.

Specification:

Ultimate torque	... 30lb-ft (41Nm)
Free speed	... 350r/min
Operating air pressure	... 90psi (6.2bar)
Average air consumption	... 4.0cfm (114L/min)
Minimum hose size	... 3/8" I.D
Air inlet	... 1/4" BSP
Weight	... 400g

Stock No.	Price each
14199	



3/8" SQ.DRIVE



3 4204BK

3/8" Sq. Dr. AIR RATCHET KIT (15 PIECE)

Ratchet ideal for most applications in the automotive workshop and is suitable for radiator, fuel pump and spark plug removal. Supplied complete in carrying case. Display carton.

Contents: • reversible ratchet • 7 chrome vanadium impact sockets size: 10, 11, 12, 13, 14, 17 and 19mm
• extension bar size: 75mm • 3 impact screwdriver bits size: 6, 7mm plain slot and No.2 cross slot • universal joint
• oil pot • 1/4" BSP nipple

Specification:

Free speed	... 150r/min
Average air consumption	... 4.0cfm (114L/min)
Weight	... 1.1kg (machine only)

Stock No.	Price per kit
52604	

3/8" SQ.DRIVE



3/8" SQ.DRIVE



3/8" SQ.DRIVE



4 5218PRO

3/8" Sq. Dr. STUBBY COMPOSITE BODY AIR RATCHET

Expert Quality, lower noise, low vibration, low weight with wobble anvil and silenced motor outlet for maximum user comfort. The composite body makes this a lightweight but rugged tool that reduces operator fatigue and the 'cold sink' effect. Display carton.

Specification:

Ultimate torque	... 30lb-ft (41Nm)
Free speed	... 350r/min
Operating air pressure	... 90psi (6.2bar)
Average air consumption	... 4.0cfm (114L/min)
Minimum hose size	... 3/8" I.D
Air inlet	... 1/4" BSP
Weight	... 400g

Stock No.	Price each
14210	

5 5224PRO

3/8" Sq. Dr. SOFT GRIP AIR RATCHET

Expert Quality, lower noise, low vibration, soft grip ratchet designed for the professional user. Rear rotating exhaust for user comfort. Rotating air inlet to prevent air lines tangling. Rubber boot around ratchet head to minimise in use damage. Display carton.

Specification:

Ultimate torque	... 50lb-ft (68Nm)
Free speed	... 150r/min
Operating air pressure	... 90psi (6.2bar)
Average air consumption	... 4.0cfm (114L/min)
Minimum hose size	... 3/8" I.D
Air inlet	... 1/4" BSP
Weight	... 1.2kg

Stock No.	Price each
47568	

2 4204B

3/8" Sq. Dr. AIR RATCHET

Ratchet ideal for most applications in the automotive workshop. Display carton.

Specification:

Ultimate torque	... 50lb-ft (68Nm)
Free speed	... 150r/min
Operating air pressure	... 90psi (6.2bar)
Average air consumption	... 4.0cfm (114L/min)
Minimum hose size	... 3/8" I.D
Air inlet	... 1/4" BSP
Weight	... 1.1kg

Stock No.	Price each
52603	