

## DIE GRINDERS



### 1 5221PRO COMPACT AIR DIE GRINDER (6mm)

- **Expert Quality**
- Low noise, low vibration • Lightweight housing
- Variable speed motor • Rotating air inlet
- Alloy motor and gear housings • Steel throttle lever
- Variable speed adjustment • Low noise motor outlet

Collet size	6mm
Free speed	25,000 rpm
Operating air pressure	90psi (6.2bar)
Average air consumption	4.0cfm (113L/min)
Vibration level	2.6M/S <sup>2</sup>
Min. hose size	3/8" (10mm)
Air inlet	1/4" BSP
Weight	0.57kg

Stock No.  
47565



### 2 5222PRO DIE GRINDER (6mm)

- **Expert Quality**
- Low noise, low vibration • Lightweight housing
- Variable speed motor • Rotating air inlet
- Alloy motor and gear housings • Steel throttle lever
- Variable speed adjustment • Low noise motor outlet

Collet size	6mm
Free speed	20,000 rpm
Operating air pressure	90psi (6.2bar)
Average air consumption	4.0cfm (113L/min)
Vibration level	2.6M/S <sup>2</sup>
Min. hose size	3/8" (10mm)
Air inlet	1/4" BSP
Weight	0.7kg

Stock No.  
47566



### 3 SFAG MINI AIR DIE GRINDER (6mm)

- Low noise, low vibration
- Variable speed • Composite body
- Reduces operator fatigue and the 'cold sink' effect
- Rotating air inlet
- Supplied with two open ended collet wrenches

Collet size	6mm
Free speed	25,000 rpm
Operating air pressure	90psi (6.2bar)
Average air consumption	7cfm (198L/min)
Vibration level	0.9M/S <sup>2</sup>
Min. hose size	3/8" (10mm)
Air inlet	1/4" BSP
Weight	0.35kg

Stock No.  
65130

## ANGLED DIE GRINDERS



### 4 5220PRO 115° COMPACT AIR DIE GRINDER (6mm)

- **Expert Quality**
- Low noise, low vibration • Lightweight housing
- Variable speed motor • Rotating air inlet
- Alloy motor and gear housings • Steel throttle lever
- Variable speed adjustment • Low noise motor outlet

Collet size	6mm
Free speed	20,000 rpm
Operating air pressure	90psi (6.2bar)
Average air consumption	4.0cfm (113L/min)
Vibration level	2.6M/S <sup>2</sup>
Min. hose size	3/8" (10mm)
Air inlet	1/4" BSP
Weight	0.64kg

Stock No.  
47564

**NEW**



### 5 DAT-ADG 90° AIR DIE GRINDER (6mm)

- Low noise, low vibration • Variable speed
- Lightweight aluminium body • Lever block trigger
- Rear exhaust • 4-speed rear regulator

Collet size	6mm
Free speed	20,000 rpm
Operating air pressure	90psi (6.2bar)
Average air consumption	4.0cfm (113L/min)
Vibration level	2.9M/S <sup>2</sup>
Min. hose size	3/8" (10mm)
Air inlet	1/4" BSP
Weight	0.53kg

Stock No.	Part No.	Description
83769	DAT-ADG	Die Grinder
27941	A4217K	6mm Collet
27942	A4217K	3mm Collet
21831	Y4217	1/8" Collet



### 6 SFAG90 90° MINI AIR DIE GRINDER (6mm)

- Low noise, low vibration
- Variable speed • Composite body
- Reduces operator fatigue and the 'cold sink' effect
- Rotating air inlet
- Supplied with two open ended collet wrenches

Collet size	6mm
Free speed	20,000 rpm
Operating air pressure	90psi (6.2bar)
Average air consumption	7cfm (198L/min)
Vibration level	1.4M/S <sup>2</sup>
Min. hose size	3/8" (10mm)
Air inlet	1/4" BSP
Weight	0.55kg

Stock No.  
65137