

RCD PROTECTION

"DAVE SAYS" QUALITY MAKES THE DIFFERENCE

When using electrical devices it's essential they're connected to the electrical supply through a RCD. Essentially an RCD detects when the electric current is unbalanced between the phase and neutral conductors. Such an imbalance can be caused by current leakage through a person who's accidentally touching a live circuit, potentially causing an lethal shock. RCD's are designed to disconnect the power supply when this happens, ensuring no electric shocks.

**1 RCD3
RCD ADAPTOR**

Tested to BS 1363 and IEC 61540

- Tested to BS 1363 and IEC 61540
- Double pole RCD contact break
- For standard 13A socket
- Rated trip current 30mA
- Trip speed 30ms (typical)

Rated voltage	230 - 250V/AC
Load	3120W (max.)
Maximum operating current	13A
Rated trip current	30mA
Trip speed	30ms (typical)

Stock
No.
69307

NEW**2 MT3B****24 HOUR MECHANICAL TIMERS (PACK OF 3)**

48 on/off settings per 24 hours. Minimum setting time 30 minutes. Manual override switch. Rated 8A/2000W. Correctly used this timer can save the user energy and money. Display packed in threes.

Order number of packs required. (3 per pack)

Stock
No.
02118

**3 DT2
7 DAY DIGITAL TIMERS (PACK OF 2)**

140 programmable on/off settings per week, countdown and random functions. AM, PM or 24 hour settings. Battery back up. Rated 8A/2000W. Correctly used this timer can save the user energy and money. Display packed in twos.

Order number of packs required. (2 per pack)

Stock
No.
44912

**4 TPE
EUROPEAN TRAVEL ADAPTORS (PACK OF 2)**

Conforms to BS5733

Allows UK and ROI three pin plugs to be used in European round two-pin sockets. Maximum current 10A. Packed two per display pack.

Order number of packs required. (2 per pack)

Stock
No.
90061

**5 TPF
UK/IRELAND PLUG ADAPTOR**

Conforms to BS1363

Allows all non UK/Ireland 2 pin plugs to work in UK and Ireland three pin plug sockets. Display packed.

Stock
No.
26447

**6
4-WAY EXTENSION LEADS**

Manufactured to BS1363 Specifications and BSI Approved

This slimline design is suitable for use with all household appliances including computers and peripherals up to and including 13A. Fitted with 13A fused three pin plug. Packed in polythene bag with header card.

Stock No.	Part No.	Cable Length
72716	ES4/1A	1M
26458	ES4/1B	5M

**7
6 WAY SURGE PROTECTED
EXTENSION LEADS**

Complies with BS1363 specifications. BSI Approved

Suitable for use with all household appliances. The anti-surge feature helps to avoid current 'spikes' damaging computers and delicate electronics. Fitted with 13A fused three pin plug. Display packed.

Stock No.	Part No.	Cable Length
26534	ES6/075	0.75M
26536	ES6/2	2.0M

**8 ES10/2T
10 WAY DOUBLE SIDED SURGE PROTECTED
EXTENSION LEAD**

Complies with BS1363 specifications. BSI Approved

Suitable for use with all household appliances. The anti-surge feature helps to avoid current 'spikes' damaging computers and delicate electronics. Supplied with base enabling the unit to be stored upright. Fitted with 2M (approx.) of cable and 13A fused three pin plug. Display packed.

Stock
No.
26537