



**1** MTC100  
**MANUAL TYRE CHANGER**

Ultra portable and ideal for use on site or at home, a must have kit for professional and DIY mechanics. Suitable for most open centred wheels. The kit includes a bead breaker and tyre iron. Great care must be taken when used on alloy wheels as Draper Tools can not accept responsibility for use on unsuitable wheels. Display packed.

Stock No.  
16395



**2** TL  
**TYRE LEVERS (450mm)**

Pair of tyre levers hot forged from EN8 steel hardened, tempered and zinc plated. Carded pair of 2. Display packed.

Stock No.  
31495



**3** WWP1  
**WHEEL BALANCE WEIGHT PLIERS (250mm)**

For fitting, removing and cutting vehicle wheel weights. Drop forged carbon steel hardened, tempered, heat treated and plated finish for corrosion protection. PVC dipped handles. Display packed.

Stock No.  
56748



**4** TVTS1  
**TYRE VALVE TORQUE DRIVER**

**Expert Quality**, allows replacement of Schrader valve cores to the correct torque. Important on vehicles with Tyre Pressure Monitoring Systems (TPMS). Max torque 0.45Nm. Display packed.

Stock No. Length  
46795 150mm



**5** 4858  
**PARTS CLEANING BRUSH (260mm)**

Plastic handle with bristle head. Display packed.

Stock No. Head Dia.  
38860 25mm



**6** DAC403  
**DIGITAL GAUGE AIR LINE INFLATOR WITH TWIN CONNECTORS**

Compliant with BS EN12645

- **Expert Quality**
- Digital air line gauge
- Highly accurate industrial quality
- Suitable for use on garage forecourts and tyre fitting bays
- Fitted with a large LCD backlit screen with multi-pressure unit and twin connectors
- Supplied with calibration certificate and two AAA batteries.

|                        |                                   |
|------------------------|-----------------------------------|
| Pressure range         | 0.3-17.2 bar/4-250psi /30-1723kPa |
| Reading Accuracy       | 0.01bar, 1kPa, 0.1psi             |
| Max inlet pressure     | 18bar, 260psi, 1800kPa            |
| Inflation flow(@13BAR) | 500l/min, 18CFM                   |
| Supply inlet           | 1/4" BSP taper (F)                |
| Hose length            | 0.53m (21")                       |

| Stock No. | Description         |
|-----------|---------------------|
| 74839     | Airline             |
| 61833     | Batteries (4 x AAA) |



**7** ALG43  
**HI-FLO AIR LINE INFLATOR WITH TWIN OPEN ENDED CONNECTOR**

Manufactured and certified to Directive 86/217/EEC

- **Expert Quality**,
- Improved MK4 version airline inflator
- Industrial quality suitable for use on garage forecourts and tyre fitting bays
- Fitted with a twin open ended connectors, 20% larger viewing window, hardier yet lighter body and increased accuracy
- Supplied with calibration certificate

|                      |                                      |
|----------------------|--------------------------------------|
| Pressure range       | 0-9.6bar/0-138psi                    |
| Air supply pressure  | min.6.9bar/100psi max.13.8bar/200psi |
| Operating Temp range | 10 to 60 degree C                    |
| Storage temp range   | 30 to 80 degree C                    |
| Supply inlet         | 1/4" BSP taper (F)                   |
| Hose length          | 0.5M (approx.)                       |

| Stock No. | Description          |
|-----------|----------------------|
| 16234     | Gauge                |
| 30769     | Sp. Hose & Connector |
| 30771     | Sp. Connector        |



**8** ALG44  
**HI-FLO AIR LINE INFLATOR WITH LOCK-ON CONNECTOR**

Manufactured and certified to Directive 86/217/EEC

- **Expert Quality**,
- Improved MK4 version airline inflator
- Industrial quality suitable for use on garage forecourts and tyre fitting bays
- Fitted with lock-on connector, 20% larger viewing window, hardier yet lighter body and increased accuracy
- Supplied with calibration certificate

|                      |                                      |
|----------------------|--------------------------------------|
| Pressure range       | 0-9.6bar/0-138psi                    |
| Air supply pressure  | min.6.9bar/100psi max.13.8bar/200psi |
| Operating Temp range | 10 to 60 degree C                    |
| Storage temp range   | 30 to 80 degree C                    |
| Supply inlet         | 1/4" BSP taper (F)                   |
| Hose length          | 0.5M (approx.)                       |

| Stock No. | Description          |
|-----------|----------------------|
| 16230     | Gauge                |
| 30770     | Sp. Hose & Connector |
| 30773     | Sp. Connector        |