


1 4766 35mm HINGE HOLE CUTTER

Manufactured from hardened and tempered tool steel. Display packed.

Stock No.
14037



2 4302B 40-120mm HOLE CUTTER

Combination shank for hand brace or power drill. Speed range 200 rpm when cutting holes above 90mm diameter increasing to 800rpm for 40mm diameter holes. The cutter has an easy to use adjustment nut, graduated beam and hardened pilot point. For wood and plastics, maximum cutting depth 30mm. Display packed.

Stock No.
31950



3 HSS ROSEHEAD COUNTERSINK BITS

Heavy duty countersink bit, made from high speed steel hardened and tempered to 55HRC for longer life. The 90° head incorporates five cutting edges and an 8mm diameter shank. Suitable for use with hand or power drills on hard or softwood, metals and plastics.

Stock No.	Part No.	Head Diameter
19234	HS12	13mm
19235	HS16	16mm



4 DB2 13mm COUNTERSINK BIT

General purpose bit for use on wood or plastics. Suitable for use with hand or power drills. Shank diameter 6mm. Display packed.

Stock No.
92526



5 COUNTERSINK BITS

Manufactured from special tool steel, hardened and tempered to 55HRC for long life. The 90° head incorporates a single finely ground fast cutting edge. Shank 6mm diameter. Suitable for use with hand or power drills on hard or softwood and plastics. Display packed.

Stock No.	Part No.	Head Diameter
10572	CS12	12mm
10573	CS16	16mm



6 B46 1/4" Sq. Dr. x 1/4" HEXAGON BIT ADAPTOR

Manufactured from chrome vanadium steel hardened, tempered with shot blast finish. Spring-loaded ball bearing for secure socket holding. Display packed.

Stock No.	Overall Length
22182	50mm



7 3.720.0 SCHRÖDER MAGNETIC BIT HOLDER

Expert Quality. 1/4" female x 1/4" male magnetic bit holder. For use in power drills and driver handles. Shaft from chrome vanadium steel hardened and tempered. Magnetic bit holder made from chrome plated brass for 6.35mm (1/4") hexagon insert bits in accordance with ISO1173. Packed in polybag.

Stock No.	Overall Length
33812	70mm



8 MAGNETIC BIT HOLDERS

1/4" male x 1/4" female magnetic bit holder for use in power drills and driver handles. Shaft (male hexagon) from chrome vanadium steel hardened and tempered with the bit holder (female hexagon) cold forged from stainless steel. Display packed.

Stock No.	Part No.	Overall Length
82407	MH/B	60mm
82408	MH150/B	150mm
82409	MH300/B	300mm



9 BIT HOLDERS WITH 'QUICK RELEASE'

1/4" hex. male x 1/4" female with quick release for use in power drills and driver handles. Carbon steel shaft (male hexagon) hardened and tempered (male hexagon) with the bit holder (female hexagon) from stainless steel. 'Quick release' collet allows bits to be expelled quickly and efficiently. Display packed.

Stock No.	Part No.	Overall Length
82410	MH/QR/60/B	60mm
82411	MH/QR/150/B	150mm



10 BCS SOCKET DRIVE ADAPTOR SET

Designed for use in conjunction with any 1/4" hexagon drive unit, i.e. hand, electric or air screwdrivers, to drive 1/4" and 3/8" square drive sockets. Comprises 1/4" hexagon x 1/4" square and 1/4" hexagon x 3/8" square adaptors. Manufactured from chrome vanadium steel hardened, tempered and chrome plated. Each square driver end incorporates a spring-loaded retaining ball for secure socket holding. Display packed.

Stock No.
50087

NEW



11 BCS/3 SOCKET DRIVE ADAPTOR SET

Designed for use in conjunction with any 1/4" hexagon drive unit, i.e. hand, electric or air screwdrivers, to drive 1/4", 3/8" and 1/2" square drive sockets. Comprises 1/4" hexagon x 1/4" square, 1/4" hexagon x 3/8" square and a 1/4" hex x 1/2" square adaptors. Manufactured from chrome vanadium steel hardened, tempered and chrome plated. Each square driver end incorporates a spring-loaded retaining ball for secure socket holding. Display packed.

Stock No.
00005



3/8" SQ.DRIVE

1/2" SQ.DRIVE



12 BIT HOLDING SOCKETS

Expert Quality. insert bit holders with spring clip and ball bearing for secure bit retention. Forged from chrome vanadium steel hardened and tempered with a micro satin finish. Display packed.

Stock No.	Part No.	Sq. Dr.	Bit Size
85125	B-BHA	1/4"	1/4"
16809	D-BH/B	3/8"	1/4"
16810	H-BH/B	1/2"	5/16"
16811	H-BH/C	1/2"	10mm