section 5 **AIR HOSES**











12M RETRACTABLE AIR HOSE REEL

- Provides 10bar/145psi working/burst pressure
- Ratchet lock system 'stoppable' every 20cm (approx)
- Attached to a 180° ceiling/wall mounting bracket

Hose size	6.5 x 10mm
Hose connection	1/4 BSP thread
Max. working/burst pressure	10 bar (145psi)
Operating temperature	-5 to 45°C

Operating temperature	5 -0 10 43
Stock No.	
15047	

2 RAH **RETRACTABLE AIR HOSE REELS**

- 3/8" PVC Hybrid hose providing greater flexibility in cold conditions
- Slow return function for user safety
- Stops at any position for user comfort
- Wall mounting on 180° swivel bracket
- Internal rewind guide prevents hose tangling

Hose size	8 x 12mm
Hose connection	1/4 BSP thread
Max. working/burst pressure	18/54 bar (261/783psi)
Operating temperature	-5 to 45°C

Stock No.	Length	
15048 15049	10M 30M	

RAH15

15M RETRACTABLE AIR HOSE REEL

- Expert Quality
- Rubber hose providing greater flexibility in cold conditions
- · Slow return function for user safety
- Stops at any position for user comfort
- \bullet Wall mounting on 180° swivel bracket

Hose size	3/8"
Hose connection	1/4 BSP thread
Max. working/burst pressure	20 bar (300psi)
Operating temperature	-5 to 45°C

Stock No.	Length	
15050	15M	







11.5M HEAVY DUTY NYLON RECOIL AIR HOSES

Hoses manufactured to BS5409 Specifications

Recoil type air hose which allows good access to working areas. For the workshop and industrial user. Supplied with spring protection guards and 360° swivel end male fittings. Maximum working pressure at 20°C; - 1.4MPa (203psi). Display packed.

Stock	Part	Hose
No.	No.	Connections
INO.	IVO.	Connections
76981	4282C	1/4" BSP male
76982	4283C	3/8" BSP male



7.6M NYLON RECOIL AIR HOSES

DIY recoil type air hose which allows good access to working areas. Supplied with spring protection guards and male brass end fittings, one 360° swivel the other fixed. Display packed.

Stock	Part	Hose
No.	No.	Connections
52662	4225/1A	1/4" BSP male
52663	4225/2A	3/8" BSP male



600mm WHIP HOSES

Manufactured to BS Specifications

Health and Safety Executive guidance regulations recommend a flexible isolating hose to be used between the air tool and coupling, thus isolating the tool's vibration. Supplied with PCL adaptor and appropriate male tailpiece. Display packed.

Stock	Part	Male	Hose	
No.	No.	Thread	I/D x O/D	
54438	4311	1/4" BSP	7 x 14mm	
54439	4312	3/8" BSP	10 x 17mm	
54440	4313	1/2" BSP	13 x 21mm	



CONNECT KIT

1/4" STANDARD AIR TOOL CONNECTION KIT

Air tool connection kit consisting of high pressure PVC hose, PCL coupling set and female coupling. Sold loose.

- Air line hose, 15.2M x 1/4" bore, Stock No. 36939
- Air line coupling set, 1/4 BSP, Stock No. 37844
- 1/4" Parallel female coupling, Stock No. 37827

Stock No. 64503