

## AIR CUT-OFF TOOLS



- 1** 5226PRO  
**REVERSIBLE AIR CUT-OFF TOOL (75mm)**  
 Manufactured to EN 12413 Specifications  
 • **Expert Quality**  
 • Low noise, low vibration • Lightweight housing  
 • Reversible mechanism • Variable speed motor  
 • Rotating air inlet • Steel throttle lever

|                         |                     |
|-------------------------|---------------------|
| Cutting wheel diameter  | 75mm                |
| Free speed              | 18,000 rpm          |
| Operating air pressure  | 90psi (6.2bar)      |
| Average air consumption | 4cfm (113L/min)     |
| Vibration level         | 2.5m/s <sup>2</sup> |
| Min. hose size          | 3/8" (10mm)         |
| Air inlet               | 1/4" BSP            |
| Weight                  | 0.9kg               |

| Stock No. | Part No. | Description       |
|-----------|----------|-------------------|
| 47569     | 5226PRO  | Cut-Off Tool      |
| 26825     | CWMF2C   | 75 x 10mm C/Wheel |

**NEW**



- 2** DAT-ACT  
**AIR CUT-OFF TOOL (75mm)**  
 • Composite housing with compact design  
 • Rear exhaust • Variable speed  
 • Lightweight aluminium housing • 360° rotating guard  
 • Safety trigger prevents accidental starts  
 • Adjustable 4-speed regulator • 360° rotating air inlet

|                         |                      |
|-------------------------|----------------------|
| Cutting wheel diameter  | 75mm                 |
| Free speed              | 20,000 rpm           |
| Operating air pressure  | 90psi (6.2bar)       |
| Average air consumption | 5cfm (141L/min)      |
| Vibration level         | 2.38m/s <sup>2</sup> |
| Min. hose size          | 3/8" (10mm)          |
| Air inlet               | 1/4" BSP             |
| Weight                  | 0.84kg               |

| Stock No. | Part No. | Description     |
|-----------|----------|-----------------|
| 84124     | DAT-ACT  | Cut-off Tool    |
| 26825     | CWMF2C   | 75 x 10mm Wheel |

## AIR ANGLE GRINDERS



- 3** 5228PRO  
**COMPOSITE AIR ANGLE GRINDER (115mm)**  
 • **Expert Quality**  
 • Low noise, low vibration • Composite body  
 • Reduces operator fatigue and the 'cold sink' effect  
 • High strength, alloy, gear housing • Steel throttle lever  
 • Rear exhaust • 9 position wheel guard  
 • Spindle lock for easy disc change

|                         |                     |
|-------------------------|---------------------|
| Disc size               | 115mm               |
| Free speed              | 12,000 rpm          |
| Operating air pressure  | 90psi (6.2bar)      |
| Average air consumption | 4.0cfm (114L/min)   |
| Vibration level         | 2.5M/S <sup>2</sup> |
| Min. hose size          | 3/8" (10mm)         |
| Air inlet               | 1/4" BSP            |
| Weight                  | 2kg                 |

| Stock No. | Part No. | Description |
|-----------|----------|-------------|
| 47572     |          |             |



**NEW**

- 4** DAT-AAG  
**AIR ANGLE GRINDER (100mm)**  
 • Safety lever trigger • Adjustable built-in regulator  
 • Auxiliary side handle • Governor mechanism  
 • Hardened steel bevelled gears • Top exhaust  
 • Low noise, low vibration • Lightweight aluminium body

|                         |                      |
|-------------------------|----------------------|
| Disc size               | 100mm                |
| Free speed              | 11,000 rpm           |
| Operating air pressure  | 90psi (6.2bar)       |
| Average air consumption | 6.5cfm (184L/min)    |
| Vibration level         | 2.43M/S <sup>2</sup> |
| Min. hose size          | 3/8" (10mm)          |
| Air inlet               | 1/4" BSP             |
| Weight                  | 1.67kg               |

| Stock No. | Part No. | Description   |
|-----------|----------|---------------|
| 83953     | DAT-AAG  | Angle Grinder |
| 27940     | A4207P   | Backing Pad   |

## 50MM AIR ANGLE GRINDER KIT



- 5** 5225PRO  
**COMPACT AIR ANGLE GRINDER KIT (50mm)**  
 • **Expert Quality**  
 • Low noise, low vibration  
 • Variable speed  
 • Lightweight body  
 • Steel throttle lever  
 • Side exhaust  
 • Alloy motor and gear housings  
 • Supplied with four grinding wheels

|                         |                     |
|-------------------------|---------------------|
| Disc size               | 50mm                |
| Free speed              | 20,000 rpm          |
| Operating air pressure  | 90psi (6.2bar)      |
| Average air consumption | 4.0cfm (114L/min)   |
| Vibration level         | 2.5m/s <sup>2</sup> |
| Min. hose size          | 3/8" (10mm)         |
| Air inlet               | 1/4" BSP            |
| Weight                  | 0.75kg              |

| Stock No. |
|-----------|
| 47570     |



- 6**  
**DEPRESSED CENTRE METAL GRINDING WHEELS (50mm)**

Resinoid bonded aluminium oxide, maximum working speed 50m/sec. For use with the Compact Air Angle Grinder Kit Stock No. 47570. Sold loose.

| Stock No. | Part No. | Grade     |
|-----------|----------|-----------|
| 48208     | AAT10    | A60-Q-BF  |
| 48209     | AAT11    | A80-Q-BF  |
| 48210     | AAT12    | A120-Q-BF |