

## TESTED TO 10,000V AND CERTIFIED TO EN-60900

High power hybrid and electric vehicles offer an ever-increasing risk of electrocution; reduce that risk with these fully insulated VDE sockets and accessories. All are manufactured from chrome vanadium steel to DIN Standard and each component has been tested to 10,000V for safe 1000V AC and 1500V DC live working, before being individually certified to EN 60900.



### 1 B6VDE-MM 1/4" SQ. DR. METRIC VDE SOCKETS

Manufactured to DIN Standard and individually certified to EN 60900

**Expert Quality**, 6 point sockets manufactured from chrome vanadium steel hardened, tempered and chrome plated. Tested to 10,000V for safe 1000V AC or 1500V DC live working. Sold loose.

Stock No.	Size
31143	4.0mm
31156	4.5mm
31164	5.0mm
31237	5.5mm
31258	6.0mm
31325	7.0mm
31435	8.0mm
31469	9.0mm
31473	10mm
31485	11mm
31490	12mm
31491	13mm
31492	14mm



### 2 D6VDE-MM 3/8" SQ. DR. METRIC VDE SOCKETS

Manufactured to DIN Standard and individually certified to EN 60900

**Expert Quality**, 6 point sockets manufactured from chrome vanadium steel hardened, tempered and chrome plated. Tested to 10,000V for safe 1000V AC or 1500V DC live working. Sold loose.

Stock No.	Size
31494	6.0mm
31500	7.0mm
31515	8.0mm
31556	9.0mm
31558	10mm
31571	11mm
31615	12mm
31660	13mm
31697	14mm
31698	15mm
31714	16mm
31720	17mm
31724	18mm
31740	19mm
31748	20mm



### 3 H6VDE-MM/B 1/2" SQ. DR. METRIC VDE SOCKETS

Manufactured to DIN Standard and individually certified to EN 60900

**Expert Quality**, 6 point sockets manufactured from chrome vanadium steel hardened, tempered and chrome plated. Tested to 10,000V for safe 1000V AC or 1500V DC live working. Sold loose.

Stock No.	Size
31756	10mm
31784	11mm
31785	12mm
31788	13mm
31789	14mm
31835	15mm
31843	16mm
31864	17mm
31869	18mm
31880	19mm
31882	20mm
31941	21mm
31951	22mm
31953	23mm
31954	24mm
31961	25mm
31964	27mm
31988	29mm
32000	30mm
32017	32mm



### 4 VDE SOFT GRIP RATCHETS

Manufactured to DIN Standard and individually certified to EN 60900

**Expert Quality**, ratchet with extended drive spindle allowing the insulation sleeve on accessories to be correctly insulated when attached to the ratchet. Tested to 10,000V for safe 1000V AC or 1500V DC live working.

Stock No.	Part No.	Sq. Dr.	Length
31091	B60VDE	1/4"	250mm
31132	D60VDE	3/8"	250mm
31137	H60VDE	1/2"	250mm



### 5 VDE EXTENSION BARS

Manufactured to DIN Standard and individually certified to EN 60900

**Expert Quality**, with spring ball bearing for socket retention. Tested to 10,000V for safe 1000V AC or 1500V DC live working. Sold loose.

Stock No.	Part No.	Sq. Dr.	Length
32042	B-EXT-VDE	1/4"	50mm
32048	B-EXT-VDE	1/4"	75mm
32078	B-EXT-VDE	1/4"	100mm
32079	B-EXT-VDE	1/4"	150mm
32098	D-EXT-VDE	3/8"	75mm
32102	D-EXT-VDE	3/8"	150mm
53209	D-EXT-VDE	3/8"	250mm
32103H-EXT-VDE/B		1/2"	75mm
32142H-EXT-VDE/B		1/2"	125mm
32144H-EXT-VDE/B		1/2"	250mm