



## **Centre Punches**

Part No.	Tip Dia. In.	Body in.	Length in.	Weight lbs.
C33A	3/32	1/4	4	.07
C33	1/8	5/16	5	.09
C34	1/8	3/8	51/4	.15
C35	3/16	1/2	6	.28
C35A	3/16	1/2	7	.33

## **Taper Punches (Starter)**

Part No.	Pin Dia. In.	Body in.	Length in.	Weight lbs.
C21	1/16	5/16	53/8	.09
C22	3/32	5/16	5%16	.09
C23	1/8	3/8	53/4	.14
C23A	5/32	3/8	6	.16
C24	3/16	3/8	63/16	.17
C27	1/4	3/8	611/16	.20
C27A	5/16	1/2	7	.36



## **Long Taper Punches (Starter)**

Part No.	Pin Dia. In.	Body in.	Length in.	Weight lbs.
C25A	1/8	5/16	8	.15
C25	5/32	3/8	8	.22
C26	3/16	7/16	9	.33
C26A	7/32	1/2	9	.42
C50	1/4	1/2	91/2	.47
C51	5/16	1/2	91/2	.50
C52	3/8	1/2	91/2	.52



## **Prick Punch**

Part No.	Tip Dia.	Body	Length	Weight
	In.	in.	in.	lbs.
C32	1/8	3/8	5	.12

Specs: CGSB 39-GP-44a. ANSI/HTI B209.1-1991.

**Think Safety** - Punches that have "mushroomed" on striking end should be ground or filed to original shape to avoid chipping.