

EXTRACTORS & TAPPING



Straight Type Extractor

Part No.	Screw, stud or bolt size	Use drill Size	Min. hole depth	Pipe Size
SE50-1	1/4", 15/16"	1/8"	3/8"	—
SE50-2	3/8"	3/16"	1/2"	—
SE50-3	7/16"	15/64"	1/2"	1/8"
SE50-4	1/2", 9/16"	15/16"	1/2"	1/4"
SE50-5	5/8"	3/8"	5/8"	3/8"
SE50-6	3/4"	15/32"	11/16"	—
SE50-7	7/8"	9/16"	11/16"	1/2"
SE50-8	1", 1 1/8"	21/32"	3/4"	1/2"
SE50-9	1 1/4", 1 3/8"	13/16"	3/4"	3/4"
SE50-10	1 1/2"	1"	1"	1"



Left-hand Spiral Tapered Flute Extractor

Part No.	Removes screw size	Use drill size
EX1	1/8" - 5/32" / 3-4mm	5/64" / 1.8mm
EX2	3/16" - 9/32" / 5-7mm	7/64" / 2.6mm
EX3	15/16" - 3/8" / 8-10mm	5/32" / 3.7mm
EX4	7/16" - 3/8" / 11-14mm	1/4" / 5.5mm
EX5	3/8" - 11/16" / 16-18mm	18/64" / 7mm
EX6	5/8" - 7/8" / 16-22mm	13/32" / 10mm



No. SE50C 5 Pieces Straight Type Extractor Set

Contains: SE50-1, SE50-2, SE50-3, SE50-4, SE50-5
Includes Pouch



No. SE70C 7 Pieces Straight Type Extractor Set

Contains: SE50-1, SE50-2, SE50-3, SE50-4, SE50-5,
SE50-6, SE50-7
Includes Pouch