


| COD. | AF mm | L (mm) | A (mm) | B (mm) | C (mm) | D (mm) | E (mm) | g | | |
|-------|-------|--------|--------|--------|--------|--------|--------|------|---|-----|
| 67919 | 27-32 | | | | | | 10 | 460 | | |
| 61713 | 30-32 | 320 | 34 | 60 | 35 | 65 | 11 | 500 | | |
| 67970 | 36-41 | | 36 | 80 | 42 | 70 | 12 | 850 | 5 | ● B |
| 67920 | 38-42 | 360 | 42 | 85 | 47 | 75 | 13 | 900 | | |
| 67972 | 41-46 | 370 | 47 | 90 | 50 | 80 | 14 | 1200 | | |
| 67974 | 46-50 | 400 | 47 | 100 | 50 | 90 | 14 | 1500 | | |

DIN 3110

CARACTERÍSTICAS / FEATURES / CARACTÉRISTIQUES

Cr-V

INCH


| COD. | AF Inch | L (mm) | A (mm) | B (mm) | C (mm) | D (mm) | E (mm) | g | | |
|-------|---------------|--------|--------|--------|--------|--------|--------|-----|----|-----|
| 60315 | 3/16-7/32 | 105 | 4 | | 5 | 15 | 3,7 | 15 | | |
| 60300 | 1/4-5/16 | 120 | 8,0 | 14 | 9,0 | 17 | 3,6 | 22 | | |
| 60301 | 5/16-3/8 | 140 | 10 | 20 | 10 | | 3,8 | | | |
| 67941 | 5/16-11/32 | | 11 | | 12 | 22 | | 38 | | |
| 67931 | 11/32-13/32 | 145 | 12 | 22 | | | 4 | | | |
| 60302 | 3/8-7/16 | 160 | 13 | | 13 | 24 | | 50 | 10 | |
| 67942 | 7/16-1/2 | | 26 | | 15 | 28 | 5,5 | 55 | | |
| 60303 | 1/2-9/16 | 175 | 14 | 27 | | | | 60 | | |
| 60304 | 9/16-5/8 | 190 | 17 | 30 | 17 | 33 | | 70 | | |
| 60305 | 19/32-11/16 | 200 | 18 | | 19 | 38 | 6,0 | 85 | | |
| 60306 | 5/8-11/16 | | 35 | | 18 | 38 | | 115 | | |
| 67943 | 5/8-3/4 | 210 | 19 | | 20 | 36 | 7,0 | 125 | | |
| 60307 | 11/16-3/4 | 220 | | 38 | | 40 | 6,0 | 130 | | |
| 60308 | 3/4-25/32 | | 39 | 21 | | 41 | 6,5 | 160 | | ● A |
| 67934 | 3/4-13/16 | | 21 | 44 | | | 7,0 | 190 | | |
| 60309 | 3/4-7/8 | 230 | | 44 | 24 | 48 | | 200 | | |
| 60310 | 13/16-7/8 | | 25 | 45 | | 50 | 7,5 | 250 | | |
| 67944 | 7/8-15/16 | 250 | 25 | 47 | 28 | | | 260 | | |
| 60311 | 15/16-1 | 260 | | 50 | | | | 330 | 5 | |
| 67945 | 15/16-1.1/8 | | 26 | | 29 | | 8,0 | 370 | | |
| 67939 | 1-1.1/16 | | | | 28 | 60 | | 390 | | |
| 60312 | 1-1.1/8 | 280 | | 55 | 30 | | | 420 | | |
| 60313 | 1.1/16-1.1/8 | | 28 | | 31 | | 8,5 | 430 | | |
| 60314 | 1.1/16-1.1/4 | 320 | | 60 | | | | 500 | | |
| 67940 | 1.1/8-1.1/4 | | 35 | | | 65 | | | | |
| 67961 | 1.3/16-1.5/16 | 300 | | 70 | 36 | | 10 | 550 | | |
| 67968 | 1.3/8-1.1/2 | | | | | 70 | | 650 | | |
| 67946 | 1.7/16-1.5/8 | 320 | 36 | | 42 | 80 | 12 | 850 | 1 | |



DIN 3110

CARACTERÍSTICAS / FEATURES / CARACTÉRISTIQUES

Cr-V