


COD.	AF mm	L (mm)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	g		
67919	27-32						10	460		
61713	30-32	320	34	60	35	65	11	500		
67970	36-41		36	80	42	70	12	850	5	● B
67920	38-42	360	42	85	47	75	13	900		
67972	41-46	370	47	90	50	80	14	1200		
67974	46-50	400	47	100	50	90	14	1500		

DIN 3110

**CARACTERÍSTICAS / FEATURES / CARACTÉRISTIQUES**

Cr-V

**INCH**


COD.	AF Inch	L (mm)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	g		
60315	3/16-7/32	105	4		5	15	3,7	15		
60300	1/4-5/16	120	8,0	14	9,0	17	3,6	22		
60301	5/16-3/8	140	10	20	10	22	3,8			
67941	5/16-11/32		11		12			38		
67931	11/32-13/32	145	12	22			4			
60302	3/8-7/16	160	13		13	24		50	10	
67942	7/16-1/2		26		15	28	5,5	55		
60303	1/2-9/16	175	14	27				60		
60304	9/16-5/8	190	17	30	17	33		70		
60305	19/32-11/16	200	18		19	38	6,0	85		
60306	5/8-11/16		35		18	38		115		
67943	5/8-3/4	210	19		20	36	7,0	125		
60307	11/16-3/4	220		38		40	6,0	130		
60308	3/4-25/32		39	21		41	6,5	160		● A
67934	3/4-13/16		21	44			7,0	190		
60309	3/4-7/8	230		44	24	48		200		
60310	13/16-7/8		25	45		50	7,5	250		
67944	7/8-15/16	250		47	28			260		
60311	15/16-1	260		50				330	5	
67945	15/16-1.1/8		26		29		8,0	370		
67939	1-1.1/16				28	60		390		
60312	1-1.1/8	280		55	30			420		
60313	1.1/16-1.1/8		28		31		8,5	430		
60314	1.1/16-1.1/4	320		60				500		
67940	1.1/8-1.1/4		35			65				
67961	1.3/16-1.5/16	300		70	36		10	550		
67968	1.3/8-1.1/2					70		650		
67946	1.7/16-1.5/8	320	36		42	80	12	850	1	



DIN 3110

**CARACTERÍSTICAS / FEATURES / CARACTÉRISTIQUES**

Cr-V