

Sockets Hexagon Pro Torque®

mm	6.3 _m □ 1/4"		10 _m □ 3/8"		12.5 _m □ 1/2"		20 _m □ 3/4"	25 _m □ 1"	CV	ZOLL INCH 1/4" 3/8" 1/2" EN PULGADAS
	short	deep	short	deep	short	deep	short	short		
3,5	2473									
4	2474	10504								
4,5	2475									
5	2476	10505								
5,5	2477	10503								
6	2478	10506								
7	2479	10507								
8	2480	10508		10528	2908	9355				
9	2481	10509			2909					
10	2482	10510	10610	10530	2910	10550				
11	2483	10511	10611	10531	2911	10551				
12	2484	10512	10612	10532	2912	10552				
13	2485	10513	10613	10533	2913	10553				
14	2486	10514	10614	10534	2914	10554				
15			10615	10535	2915	10555				
16			10616	10536	2916	10556				
17			10617	10537	2917	10557				
18			10618	10538	2918	10558				
19			10619	10539	2919	10559	3419			
20					2920	10560				
21					2921	10561	3421			
22					2922	10562	3422			
23							3423			
24					2924	10564	3424			
26					2926	10566	3426			
27			10627		2927	10567	3427			
28					2928	10568				
30					2930	10570	3430			
32					2932	10572	3432			
33							3433			
34					2934		3434			
35					2935		3435			
36					2936		3436	3736		
38							3438			
41							3441	3741		
42							3442			
44							3444			
46							3446	3746		
48							3448			
50							3450	3750		
55							3455	3755		
60							1207-60	3760		
65								3765		
70								3770		
75								3775		
80								3780		

Sockets Hexagon Pro Torque® | Inch sizes

Inch	6.3 _m □ 1/4"		12.5 _m □ 1/2"	Inch	short	CV	ZOLL INCH 1/4" 3/8" 1/2" EN PULGADAS
	short	deep	short				
5/32"	10650			1"	2787		
3/16"	10651			1.1/16"	2784		
7/32"	10652			1.1/8"	2788		
1/4"	10653	10670		1.1/4"	2786		
9/32"	10654						
5/16"	10655	10671					
11/32"	10656						
3/8"	10657	10672	2770				
7/16"	10658	10673	2771				
1/2"	10659	10674	2772				
9/16"			2773				
5/8"			2774				
11/16"			2775				
3/4"			2776				
13/16"			2777				
7/8"			2778				
15/16"			2779				

Quick-Finder

Sockets

Quick-Finder

QF1