

10-piece Special Socket Set with Inside Tooth for Grooved Nuts, 26-88 mm 12.5 □ 1/2

- for gentle loosening groove nuts
- suitable at e.g. bearing nut
- 1/2" drive, length 60 mm

all dimensions in mm

| insideØ D2 | outsideØ D1 | tooth width ZB | tooth length ZL |
|------------|-------------|----------------|-----------------|
| 20.0 | 26.0 | 2.8 | 2.5 |
| 23.5 | 31.0 | 2.8 | 3.0 |
| 26.5 | 34.0 | 3.8 | 2.5 |
| 29.5 | 38.0 | 4.8 | 2.5 |
| 34.5 | 42.0 | 3.8 | 3.5 |
| 40.5 | 50.0 | 4.8 | 3.5 |
| 46.5 | 58.0 | 4.8 | 4.0 |
| 59.5 | 75.0 | 5.8 | 4.5 |
| 65.8 | 82.0 | 5.8 | 5.0 |
| 71.8 | 88.0 | 5.6 | 5.0 |



Item #
8266

PRO +

5-piece Groove Nut Socket Set 12.5 □ 1/2

- suitable for Mercedes differential, gear and rear axle flange
- for Mercedes series 107 - 114 - 115 - 116 - 126 etc.
- allows gentle loosening and tightening using a torque wrench
- 1/2 "drive

Item #
67220

PRO +



Stud Extractor

- suitable for damaged or broken studs with a diameter 6,3 to 14 mm (1/4" to 9/16")
- adjustable via 19 mm socket

Item #
1903

PRO +



Stud Bolt Extractor, 6 - 19 mm

- for loosening stuck studs
- suitable for loosening and tightening
- suitable for studs diameter from 6 to 19 mm
- knurled and hardened clamp wheel

Item #
8799

PRO

