

MAB 525



Core drill:
 ø: 50 mm
 L: 30 mm
 L: 55 mm
 L: 75 mm

Twist drilling:
 ø: 20 mm
Reaming:
 ø: 20 mm

Countersinking:
 ø: 50 mm
Thread cutting:
 ø: M20


Motor output: 1600 Watt
 Voltage: 230 V AC, 50-60 Hz
 Stroke: 160 mm
 Magnet size: 90 x 180 x 48 mm
 Weight: 16 kg

Quick change drill chuck system: KEYLESS, 19 mm (3/4")
 Morse taper: MT 3
 Speed range 1: 70 – 280 min⁻¹
 Speed range 2: 180 – 580 min⁻¹
 Permanent internal lubrication: ●
 Torque control: ●
 Full wave control electronics: ●
 Magnet indicator: ●
 Overheating protection: ●
 CW/CCW rotation: ●
 Carbon brush wear control: ●

MAB 525 230 V

MAB 525 110/125 V

MAB 525 SB



Core drill:
 ø: 50 mm
 L: 30 mm
 L: 55 mm
 L: 75 mm

Twist drilling:
 ø: 20 mm
Reaming:
 ø: 20 mm

Countersinking:
 ø: 50 mm
Thread cutting:
 ø: M20

Motor output: 1600 Watt
 Voltage: 230 V AC, 50-60 Hz
 Stroke: 160 mm
 Magnet size: 90 x 180 x 48 mm
 Weight: 16 kg

Quick change drill chuck system: KEYLESS, 19 mm (3/4")
 Morse taper: MT 3
 Speed range 1: 70 – 280 min⁻¹
 Speed range 2: 180 – 580 min⁻¹
 Permanent internal lubrication: ●
 Torque control: ●
 Full wave control electronics: ●
 Magnet indicator: ●
 Overheating protection: ●
 CW/CCW rotation: ●
 Carbon brush wear control: ●
 Swivel Base, adjustment feature: ●

MAB 525 SB 230 V

MAB 525 SB 110/125 V

MAB 825



Core drill:
 ø: 100 mm
 L: 30 / 55 mm
 L: 75 / 110 mm

Twist drilling:
 ø: 31,75 mm
Reaming:
 ø: 31,75 mm

Countersinking:
 ø: 50 mm
Thread cutting:
 ø: M30

Motor output: 1800 Watt
 Voltage: 230 V AC, 50-60 Hz
 Stroke: 255 mm
 Magnet size: 110 x 220 x 54 mm
 Weight: 25 kg

Quick change drill chuck system: KEYLESS, 19 mm (3/4")
 Industrial arbor: MT 3, 32 mm (1 1/4")
 Morse taper: MT 3
 Speed range 1: 40–110 min⁻¹ 2: 65–175 min⁻¹
 Speed range 3: 140–360 min⁻¹ 4: 220–600 min⁻¹
 Friction clutch: ●
 Permanent internal lubrication: ●
 Torque control: ●
 Full wave control electronics: ●
 Magnet indicator: ●
 Overheating protection: ●
 CW/CCW rotation: ●
 Carbon brush wear control: ●

MAB 825 230 V

MAB 825 110/125 V

Scope of delivery MAB 525 and MAB 525 SB: 1 Magnetic core drilling machine · 1 Quick change drill chuck system KEYLESS, 19 mm Weldon (3/4") · 1 Tapping adapter ZGA 010, ZGA 012, ZGA 016 · 1 Ejector ZAK 075, ZAK 090 · 1 Hard protective case · 1 Safety chain · 1 Taper drift MT 3/B16 · 1 Gear rim drill chuck 1 - 13 mm · 1 Drill drift MT 3 · 1 Operating manual