

ELECTRONIC OUTSIDE MICROMETER

Code	Range
3101-25	0-25mm/0-1"
3101-50	25-50mm/1-2"
3101-75	50-75mm/2-3"
3101-100	75-100mm/3-4"
3101-125	100-125mm/4-5"
3101-150	125-150mm/5-6"
3101-175	150-175mm/6-7"
3101-200	175-200mm/7-8"
3101-225	200-225mm/8-9"
3101-250	225-250mm/9-10"
3101-275	250-275mm/10-11"
3101-300	275-300mm/11-12"
Code	Range
3101-753	0-75mm/0-3" (3pcs)
3101-1004	0-100mm/0-4" (4pcs)
3101-1506	0-150mm/0-6" (6pcs)



- IP65 protection
- Thimble graduation: 0.01mm (option: 0.0001")
- Reading in metric and inch
- Resolution: 0.001mm/0.00005"
- Buttons: on/off, data set, mm/inch, ABS/INC, data output
- SR44 battery, with one spare battery, auto power off
- RS232 output, supplied with data output cable, ratchet stop, carbide tips
- DIN863
- With battery cover wrench, spare spherical anvil and zero adjusting wrench
- Supplied with standard rods
- Packed in plastic box or wooden box

ELECTRONIC OUTSIDE MICROMETER



Code	Range	Code	Range
3108-25	0-25mm	3108-1	0-1"
3108-50	25-50mm	3108-2	1-2"
3108-75	50-75mm	3108-3	2-3"
3108-100	75-100mm	3108-4	3-4"
3108-125	100-125mm	3108-5	4-5"
3108-150	125-150mm	3108-6	5-6"
3108-175	150-175mm	3108-7	6-7"
3108-200	175-200mm	3108-8	7-8"
3108-225	200-225mm	3108-9	8-9"
3108-250	225-250mm	3108-10	9-10"
3108-275	250-275mm	3108-11	10-11"
3108-300	275-300mm	3108-12	11-12"
Code	Range	Code	Range
3108-753	0-75mm (3pcs)	3108-33	0-3" (3pcs)
3108-1004	0-100mm (4pcs)	3108-44	0-4" (4pcs)
3108-1506	0-150mm (6pcs)	3108-66	0-6" (6pcs)

- Reading in metric or inch, without mm-in conversion
- Resolution: metric 0.001mm
inch 0.00005"
- Buttons: on/off, data set, ABS/INC
- IP54 protection
- SR44 battery, with one spare battery, auto power off
- Ratchet stop, carbide tips
- DIN863
- With battery cover wrench, spare spherical anvil and zero adjusting wrench
- Supplied with standard rods
- Packed in plastic box or wooden box