

ELECTRONIC OUTSIDE MICROMETER

Code	Range
3109-25	0-25mm/0-1"
3109-50	25-50mm/1-2"
3109-75	50-75mm/2-3"
3109-100	75-100mm/3-4"
3109-125	100-125mm/4-5"
3109-150	125-150mm/5-6"
3109-175	150-175mm/6-7"
3109-200	175-200mm/7-8"
Code	Range
3109-33	0-75mm/0-3" (3pcs)
3109-44	0-100mm/0-4" (4pcs)
3109-66	0-150mm/0-6" (6pcs)



- Resolution: 0.001 mm/0.00005"
- Buttons: on/off, data set, mm/inch, ABS/INC
- SR44 battery, with one spare battery, auto power off
- Ratchet friction thimble, carbide tips
- DIN863
- With battery cover wrench and spare spherical anvil
- Supplied with standard rods
- Packed in plastic box or wooden box

ELECTRONIC OUTSIDE MICROMETER

Code	Range
3103-25	0-25mm/0-1"
3103-50	25-50mm/1-2"
3103-75	50-75mm/2-3"
3103-100	75-100mm/3-4"
3103-125	100-125mm/4-5"
3103-150	125-150mm/5-6"
3103-175	150-175mm/6-7"
3103-200	175-200mm/7-8"
3103-225	200-225mm/8-9"
3103-250	225-250mm/9-10"
3103-275	250-275mm/10-11"
3103-300	275-300mm/11-12"
Code	Range
3103-753	0-75mm/0-3" (3pcs)
3103-1004	0-100mm/0-4" (4pcs)
3103-1506	0-150mm/0-6" (6pcs)



- Thimble graduation: 0.01 mm (option: 0.0001")
- Resolution: 0.001 mm/0.00005"
- Buttons: metric-inch conversion, data set
- IP54 protection
- SR44 battery, with one spare battery, auto power off
- Carbide tips
- DIN863
- With battery cover wrench, spare spherical anvil and zero adjusting wrench
- Supplied with standard rods
- Packed in plastic box or wooden box